

## Focus Motor Installation

Step 1: Remove lower knob.



Step 2: Remove lower left screw.



Step 3: Remove this focus knob using supplied allen wrench.



Step 4: Install gear as shown using supplied allen wrench. Gear should almost touch body of focuser (1/2 mm space between body and gear).



Step 5: Install motor using supplied screw while pressing down on motor bracket with thumb as shown. Tighten motor bracket screw VERY TIGHTLY to prevent motor bracket from rotating.



Step 6: Look inside gear housing and make sure both gears are aligned. If not, loosen motor bracket screw and rotate motor bracket until aligned, then retighten motor bracket screw VERY TIGHTLY.



Step 7: Plug focus motor into nFOCUS and run forwards/backwards so gears mesh properly, recheck motor bracket to screw make sure it is VERY TIGHT.



Step 8: Ready to go!



**5 Year limited warranty: Rigel Systems, 26850 Basswood Ave, Rancho Palos Verdes CA, 90275** warrants to the original consumer purchaser of its product that the product will be free of defects in material or workmanship 5 years from the date of purchase under normal use. During this warranty period, **Rigel Systems** will, at its option, repair or replace the product without charge for parts or labor when delivered to **Rigel Systems** with proof of the date of purchase and a statement of the problem with the product. Shipping and handling charges to **Rigel Systems** are your responsibility. This warranty does not apply if the product has been altered or repaired by anyone other than **Rigel Systems** or has been subjected to purchaser abuse, accident, negligence or damage subsequent to purchase including battery damage to product. This warranty excludes incidental or consequential damages resulting from the product or use of the product. The product is not a toy. Keep away from children.